



## DEWATERING PUMP

### DEWATERING PUMP CUTTER

**SCS75 | SCS75T | SCS180 | SCS180T**

#### PRODUCT DESCRIPTION

For pumping sewage water with tougher, large concentration of solid particles.

Motor Housing : Stainless Steel	Shaft	: AISI304 SS
Impeller : Cast Iron	Seal	: Double Mechanical Seal
Insulation : Class B	Protection	: IP68
Pump Body : Cast Iron	Supplied with 10 meters cable & float switch	
Motor Winding: Copper		

#### TECHNICAL FEATURES

TECH. FEATURES	SCS75	SCS75T	SCS180	SCS180T
Power	0.75kW / 1HP	0.75kW / 1HP	1.8kW / 2.4HP	1.8kW / 2.4HP
Voltage	220V - 240V	380V(3 Phase)	220V - 240V	380V(3 Phase)
Frequency	50 Hz	50 Hz	50 Hz	50 Hz
RPM	2860	2860	2860	2860
Max Head	7.5 Meter	7.5 Meter	12 Meter	12 Meter
Max Discharge	250 l/min	250 l/min	500 l/min	500 l/min
Outlet	2"	2"	3"	3"

**UAE • OMAN • QATAR • BAHRAIN • KUWAIT**

