



DEWATERING PUMP

DEWATERING PUMP SEWAGE

**SSS50 | SSS100 | SSS200L | SSS200H
SSS300T**

PRODUCT DESCRIPTION

For pumping the dirty water of hotels, residence & treatment tanks

Motor Housing	: Stainless Steel	Shaft	: AISI304 SS
Impeller	: Cast Iron	Seal	: Double Mechanical Seal
Insulation	: Class B	Protection	: IP68
Pump Body	: Cast Iron	Supplied with 10 meters cable & float switch	
Motor Winding	: Copper		

TECHNICAL FEATURES

TECHNICAL FEATURES	SSS50	SSS100	SSS200L	SSS200H	SSS300T
Power	0.37 kW / 0.5 HP	0.75 kW / 1 HP	1.5 kW / 2 HP	1.5 kW / 2 HP	2.2 kW / 3HP
Voltage	220 V - 240 V	220 V - 240 V	220 V - 240 V	220 V - 240 V	380 V (3 Phase)
Frequency	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz
RPM	2860	2860	2860	2850	2850
Max Head	8 Meter	10 Meter	22 Meter	18 Meter	16.3 Meter
Max Discharge	250 l/min	350 l/min	270 l/min	470 l/min	800 l/min
Max Solid Passage	15 mm	25 mm	25 mm	20 mm	40 mm
Outlet	1",1.25",1.5"	2"	1.5"	2"	4"

UAE • OMAN • QATAR • BAHRAIN • KUWAIT

