

DOMESTIC PUMPS

MONOBLOCK PUMP



SCML150 | SCML200 | SCML300
SCML300S | SCML300T | SCML500T

PRODUCT DESCRIPTION

For Pumping high flow of Clean Water in Residence, Garden and Industries.

Motor Housing : Aluminium	Pump Body : Cast Iron
Motor Winding : Copper	Impeller : Brass
Shaft : AISI304	Mechanical Seal : Carbon/Ceramic
Insulation : Class F	Protection : IP44
Max Suction : 9 Meter	Heavy duty continuous run

TECHNICAL FEATURES

TECHNICAL FEATURES	SCML150	SCML200	SCML300	SCML300S	SCML300T	SCML500T
Power	1.5 HP / 1.1 kW	2 HP / 1.5 kW	3 HP / 2.2 kW	3 HP / 2.2 kW	3 HP / 2.2 kW	5.5 HP / 4 kW
Rated Voltage	220 V	220 V	220 V	220 V	380 V(3 Phase)	380 V(3 Phase)
Frequency	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz
Max Operating Temp.	50°C	50°C	50°C	50°C	50°C	50°C
Max Head	20 Meter	26 Meter	33 Meter	15 Meter	16 Meter	17 Meter
Max Discharge	400 l/min	450 l/min	450 l/min	950 l/min	950 l/min	1850 l/min
Connection	2"x2"	2"x2"	2"x2"	3"x3"	3"x3"	4"x4"

UAE • OMAN • QATAR • BAHRAIN • KUWAIT

