



SUBMERSIBLE PUMP

SUBMERSIBLE OPEN WELL PUMP

SCM4A | SCM6A | SCM8A

PRODUCT DESCRIPTION

For Pumping water from Open wells, Tanks and Reservoirs.

Pump & Motor Housing : Stainless Steel	Impeller : P.P.O
Stator : Copper Winding	Mechanical Seal: Silicon/Carbide/Graphite
Shaft : AISI304	Protection : IP55
Protection : IP68	Supplied with BS Plug and Float Switch

TECHNICAL FEATURES

TECHNICAL FEATURES	SCM4A	SCM6A	SCM8A
Power	0.75 kW/1 HP	1.1 kW/1.5 HP	1.8 kW/2.4 HP
Voltage	220 V- 240V	220 V- 240V	220 V- 240V
Frequency	50 Hz	50 Hz	50 Hz
Capacitor	30 µf	35 µf	45 µf
RPM	2850	2850	2850
Insulation	B	B	B
Max Head	43 Meter	65 Meter	85 Meter
Max Discharge	130 l/min	130 l/min	130 l/min
Cable	3 Corex1 Sqmm	3 Corex1 Sqmm	3 Corex1.5 Sqmm
Cable Length	30 Meter	40 Meter	40 Meter
Outlet	1.25"	1.25"	1.25"

UAE • OMAN • QATAR • BAHRAIN • KUWAIT

